

POMPE VIDE CAVE BROYEUR



REF	DIAMETRE	CARACTERISTIQUE
V1100F	2"	1,5HP/1,1KW
V1500F	2"	2HP/1,5KW
V2200F	2/ 1/2"	3HP/2,2KW



REF	DIAMETRE	kw ET HP	MAX HEAD
V750	2"	0,75KW 1HP	17M
28/2	2"	1,1KW 1,5HP	28M
39/3	2"	1,5KW 2HP	42M
50/4	2"	2,2KW 3HP	53M

POMPE VIDE CAVE PLASTIQUE



W	V	MAX HEAD	DIAMETRE
250	220V	5M	1"
400	220V	5M	1"
500	220V	7M	1"
750	220V	8M	1"



REF	W	VOLTAGE	DIAMETRE
AB9-9	370	12V ET 24V	1"



REF	W	VOLTAGE	DIAMETRE
AB9-9	37	12V	1"



MODEL	POWER		H.Max	Q.Max	Packing Dimension	G.W	Packing
	KW	HP	m	L/min	mm	kg	Qty.
DFS-P250	0.25	0.35	5	70	210x180x320	4.5	2300
DFS-P400	0.4	0.55	6	120	210x180x320	4.7	2300
DFS-P500	0.55	0.75	7.5	150	210x180x320	5.5	2300
DFS-P750	0.75	1	8.5	190	210x180x340	6	2100



MODEL	Voltage	Power		Max.Head	Max.Flov	Outlet
	V	KW	HP	m	L/min	inch
QDX1.5-32-0.75SF	220	0.75	1	33	125	1
QDX8-18-0.75SF	220	0.75	1	20	233	1.5